





Peeling, coring and cutting machine

Model PINCYL8
Pineapple

The semi-automatic cylinder and coring machine is suitable for pineapples. Only one operator is needed for the infeed of the product. The machine does its work in three steps: removal of top and bottom, coring and finally cutting the cylinders. To facilitate the process and comply with hygiene guidelines, the cut product and waste are ejected separately onto conveyor belts. The construction of the machine consists entirely of stainless steel and, where necessary, is made of food-safe material. Moreover, all components are easily interchangeable. An option on the machine is to add different cutting operations. The cutting operations possible on this machine are cutting rings, segments and wedges.



BRAND



SPECIFICATIONS

CAPACITY	10 - 12 pieces p/min
OPERATORS	1
DIMENSIONS (LXWXH)	1460 x 1500 x 2521 mm
WEIGHT	1100 kg
POWER	2.2 kW
AIR PRESSURE / CONSUMPTION	50 l/min
WATER PRESSURE / CONSUMPTION	-
CORING DIAMETER	Ø25 / Ø30 / Ø35 mm
SLICE THICKNESS	12 / 24 mm
CYLINDER DIAMETER	Ø80 / Ø85 / Ø90 mm
NUMBER OF WEDGES	4 / 5 / 6 / 8 / 10 / 12



We have the expertise